

SPLIT UNITS FOR LOW-TEMPERATURE PREMISES 12-18°C

R 410 A

CSCF-LL

COOLING

OUTDOOR LOW AMBIENT TEMPERATURE



The CSCF-LL range of split air-conditioners is designed for 'low-temperature' air conditioning, with temperatures between 12 and 18°C, for premises such as wine cellars, florists' storerooms, bin storage units, etc.

Maintaining a temperature of between 12 and 18°C helps to limit the growth of harmful bacteria, therefore ensuring better standards of hygiene.

The interior unit can be mounted vertically against a wall as standard, or ceiling mounted in order to keep maximum floor space free.

Remote control 70250076 ou K 60 D 025 Z, to control the temperature only

Remote hygrothermostat K 60 D 047 Z, To control :

- the dehumidifier (can be piloted by an humidifier – non supplied)
- and the temperature. In that case, the accessory "electrical heater" is obligatory

The unit works permanently in order to maintain the wanted temperature (differential ≈ 1k)



Automatic remote control
K 60 D 025 Z



Manual remote control
70250076



Remote hygrothermostat
K 60 D 047 Z

ACCESSORIES

Type	Model	Code
Manual remote control RAB 30	TAF 208 - 308 - 408	70250076
Automatic remote control	TAF 208 - 308 - 408	K 60 D 025 Z
Remote hygrothermostat	TAF 208 - 308 - 408	K 60 D 047 Z
Remote sensor for electronic remote control	TAF 208 - 308 - 408	K 60 D 028 Z
Remote sensor in a box for electronic remote control	408AF 208 - 308 -	K 60 D 033 Z
Electrical heating	2 kW - 230/1/50	TAF 208 - 308
		TAF 408
	3 kW - 230/1/50	TAF 208 - 308
		TAF 408
Wall support for indoor unit	TAF 208	K 60 C 852 Z
	TAF 308	K 60 C 862 Z
	TAF 408	K 60 C 853 Z
		K 60 C 863 Z
Wall support for outdoor unit	TAF 208	K 60 U 023 Z
	TAF 308	K 60 U 024 Z
	TAF 408	K 60 U 028 Z
Wall support for outdoor unit	GRF 98/128	K 70 U 001 T
	GRF 188	K 60 U 035 T